

WGAC-95

GRANULAR COAL BASED ACTIVATED CARBON

WGAC-95 is a high activity Granular Activated Carbon manufactured by high temperature steam activation from selected grades of bituminous coal.

WGAC-95 is suitable for use in a wide variety of liquid purification and applications such as municipal drinking water treatment, beverage manufacture and process water preparation.

The well-developed transport and adsorption pore structure of WGAC-95 ensures high performance in a wide range of water treatment applications. The excellent wettability and high density provides improved adsorption per unit volume.

SPECIFICATION

Iodine number	min	950	mg/g
Moisture content	max	5	%
Total ash content	max	15	%
Wettability	min	95	%
Hardness	min	95	%

TYPICAL PROPERTIES

Surface area	1000	m ² /g
Methylene blue number	280	mg/g
Total pore volume	1.04	cm ³ /g
Water soluble ash	0.2	%
Apparent density	490	kg/m ³
pH	8-11	

AVAILABLE SIZES

6x12	(1.70-3.35 mm)	min	90	%
8x16	(1.18-2.36 mm)	min	90	%
8x30	(0.60-2.36 mm)	min	90	%
12x40	(0.425-1.70 mm)	min	90	%
20x50	(0.30-0.85 mm)	min	90	%

ADVANTAGES

- Excellent adsorption capacity
- High density
- High Wettability
- Excellent hardness
- Suitable for reactivation
- Low dust
- NSF 61 Certified
- EN 12915 Approved
- ISO Certified 14001:2015
- ISO Certified 9001:2015

STANDARD PACKAGING

- 25 kg sacks
- 500 kg big bags



NOTICE:

This information is offered solely for your consideration and verification. It has been gathered from reference materials and/or test procedures and is believed to be true and accurate. None of this information shall constitute a warranty or representation, expressed or implied, for which we assume legal responsibility or that the information or goods described is fit for any particular use either alone or in combination with other goods or processes.

Elektravägen 53
SE-126 30 Hägersten, Sweden
+46 10 252 30 00
www.mellifiq.com



© Water Maid



watermaid
a MELLIFIQ brand