

WME-90

GRANULAR ACTIVATED CARBON

WME-90 is a high activity Granular Activated Carbon manufactured by from selected raw materials.

WME-90 is suitable for use as a catalyst support in alkaline environments commonly found in oil refineries and natural gas processing plants where gas sweetening is required.

ADVANTAGES

- High purity
- Excellent catalyst support
- Low density
- Low dust
- Alkali resistant

STANDARD PACKAGING

- 300 kg big bags

PROPERTIES

Iodine number	min	900	mg/g
Moisture (as packed)	max	5	%
	type	2	%
Ash Content	max	3	%
Density	max	330	kg/m ³

SIZE DISTRIBUTION

Larger than 10	type	1	%
10x20	type	40-60	%
20x30	type	40-60	%
Smaller than 30	type	2	%
Larger than 30	type	98	%



NOTICE:

This information is offered solely for your consideration and verification. It has been gathered from reference materials and/or test procedures and is believed to be true and accurate. None of this information shall constitute a warranty or representation, expressed or implied, for which we assume legal responsibility or that the information or goods described is fit for any particular use either alone or in combination with other goods or processes.

Elektravägen 53
SE-126 30 Hägersten, Sweden
+46 10 252 30 00
www.mellifiq.com



© Nodora



Nodora
a MELLIFIQ brand